

September 13, 2002

Technical Intelligence Note, US Department of Energy, Office of Intelligence, 'Iraq: Recent Aluminum Tube Procurement Efforts'

Citation:

"Technical Intelligence Note, US Department of Energy, Office of Intelligence, 'Iraq: Recent Aluminum Tube Procurement Efforts'", September 13, 2002, Wilson Center Digital Archive, Freedom of Information Act Releases. Obtained and contributed by William Burr for NPIHP Research Update No. 25.

https://wilson-center.drivingcreative.com/document/119227

Summary:

Although the Department of Energy dissented against other Departments' opinions on the Iraqi aluminum tubes its intelligence office went along with the prevailing view that Iraq was trying to "rejuvenate" its nuclear program.

Credits:

This document was made possible with support from Carnegie Corporation of New York (CCNY)

Original Language:

English

Contents:

Original Scan

OCHR/51-

DO€



Office of Intelligence Technical Intelligence Note

TIN000108

September 13, 2002

Iraq: Recent Aluminum Tube Procurement Efforts



Scope Note

Hussein is seeking to reconstitute Iraq's nuclear weapons program. One such potential indicator is the aluminum tubes issue discussed in this paper. While we continue to assess that this acquisition effort probably is motivated by a conventional military rather than nuclear application, we judge that other indicators collectively do indicate intention to rejuvenate Iraq's nuclear weapons program.

Key Judgments

Iraq is continuing in its attempt to procure large numbers of seamless, 7075 T6 aluminum alloy tubes. These tubes could be modified for use as centrifuge rotors. However, technical experts at DOE and the National Laboratories believe other conventional military uses are more plausible. The tubes are very similar to those used by Iraq in the past to manufacture rocket casings, including the Nassr-81 rocket. In 1996, Iraq declared to the UN and the IAEA an in-country stockpile of over 65,000 such 7075-T6 aluminum alloy tubes. Regardless of their end use, any Iraqi inventories of such tubes (including new acquisitions) are required to be declared and subjected to UN/IAEA monitoring under the terms of existing UN Security Council resolutions.

(9 City)

Derivative Classifier
Decissify on: X1
Derivatively classified by: Multiple Sources

CODE 300


SECRETE OCNUR


P(0) DOE


DOE P.C.

DOE 3

Comments and queries are welcome and may be addressed to DOE, Office of Intelligence








DOE DOE

E(SANE) In contrast, the dimensions of the tubes are consistent with applications to rocket motors previously declared by Iraq. According to research by DOE and National Laboratory technical analysts, many conventional rocket motors are approximately 80-85 mm in outer diameter, 900 mm in length, and are composed of high-strength aluminum alloys.

- 6 (S//NF) The Nassr-81 is made at Nassr State Establishment. Iraq has manufactured large numbers of these 81-mm rockets since the 1980s. When inspected by the IAEA in 1996, the Iraqis had sixty-six thousand four hundred and thirty-seven 7075 T6 aluminum tubes with the same dimensions as the tubes originally sought by Iraq last year. IAEA inspectors reportedly reviewed this case and determined that the factory was indeed producing rockets for the Nassr-81. This 81-mm rocket was declared by Iraq in its 1996 "Full, Final, and Complete Disclosure" on missiles to the UN following the Gulf war.
- (S//NF)-These procurements are being conducted at a security level consistent with much
 of Iraq's military and industrial procurement activities, and not at a level that we would
 expect for WMD procurements.

OC,NF) Furthermore, the reported pressures, stresses, and method of testing are consistent with rocket motor testing. Unlike centrifuges, which develop their stresses from the high speed of rotation, solid-fuel rocket motors develop stresses from internal pressure, and hydrostatic testing is typical for rocket motor cases.



(S) DC;NF) Several other features of the latest reporting also appear to track with an intended use in solid-fuel rocket motor cases.

(5 ACC,NF) The tube wall thickness. The tube wall's thickness does not correspond with what we would expect to see in centrifuge designs — except possibly a Beams-type centrifuge — it is too thick for the design we assess that Iraq is most likely to be pursuing today, the Zippe design.

Although Iraq has experimented with a Beams-type design in the past, it abandoned that design in favor of the Zippe design. The significantly

SECRET

OC,NF#X1

DOE)

DOE b(3)

DOE()

thicker tube wall substantially increases the mass of the assembled rotor, with attendant undesirable increases in the load on the bottom bearing and damping system.

DOE bis

30

the pressure rating of the tubes than the ultimate balance of tubes suggests that the end use may not be a centrifuge rotor.

DOE -

63

anodized on the outside rather than the inside. We assess that the requirement for anodization is not necessary — and is even problematic — for centrifuges. Bare aluminum is resistant to UF₆ and anodization is unnecessary for corrosion resistance, either for the aluminum rotors or for the thousands of feet of aluminum piping in a centrifuge facility. Instead, anodization would likely introduce uncertainties into the design that would need to be resolved before a centrifuge could be operated. In contrast, anodization is a standard practice in missile construction in order to preclude galling of aluminum parts as they pass each other during launch.